

# Safety Data Sheet

acc. to OSHA HCS


Printing date 03/30/2021

Reviewed on 03/30/2021

## 1 Identification

- **Product identifier**
- **Trade name:** FOX Suspension Fluid 4WT
- **Application of the substance / the mixture**  
Only for proper handling.  
Fork oil
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
MOTOREX AG  
Bern-Zürich-Strasse 31, Postfach  
CH-4901 Langenthal  
Tel. +41 (0)62 919 75 75  
[www.motorex.com](http://www.motorex.com)
- **Information department:** [msds@motorex.com](mailto:msds@motorex.com)
- **Emergency telephone number:**  
USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**  
  
GHS08
- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
Distillates (petroleum), hydrotreated light naphthenic  
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based  
Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics  
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
- **Hazard statements**  
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements**  
P301+P310 If swallowed: Immediately call a poison center/doctor.  
P331 Do NOT induce vomiting.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0  
Fire = 1  
Reactivity = 0

(Contd. on page 2)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

**Trade name: FOX Suspension Fluid 4WT**

(Contd. of page 1)

**· HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	25-50%
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2	Distillates (petroleum), hydrotreated light naphthenic Asp. Tox. 1, H304	≥25-≤50%
CAS: 72623-87-1 EINECS: 276-738-4 Index number: 649-483-00-5	Lubricating oils (petroleum), C20-50, hydro-treated neutral oil-based Asp. Tox. 1, H304	≥1-≤7.5%
CAS: 64742-46-7 EINECS: 265-148-2	Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics Asp. Tox. 1, H304	≥0.25-≤2.5%

**· Additional information:**

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346.

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Remove residues with soap and water.  
Remove contaminated clothing immediately.
- **After eye contact:**  
Rinse opened eye for several minutes under running water.  
Consult a physician if irritation develops.
- **After swallowing:**  
Do not induce vomiting. Do not take in resorption stimulating agents.  
Consult a physician who will decide on need and method of emptying the stomach.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

US

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 2)

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**  
In case of fire carbon, sulphur and nitrogen oxides can be formed.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**  
No dangerous substances are released.  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

#### · PAC-1:

97-88-1	n-butyl methacrylate	19 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
140-88-5	ethyl acrylate	8.3 ppm

#### · PAC-2:

97-88-1	n-butyl methacrylate	210 mg/m <sup>3</sup>
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
140-88-5	ethyl acrylate	36 ppm

#### · PAC-3:

97-88-1	n-butyl methacrylate	1,300 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
140-88-5	ethyl acrylate	240 ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.
- **Information about protection against explosions and fires:**  
Do not heat above flash point.

(Contd. on page 4)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

**Trade name: FOX Suspension Fluid 4WT**

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Store containers closed and protect against rain, dust, heat and other atmospheric influences.  
Keep receptacle tightly sealed.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

### \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:**  
No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.
- **Breathing equipment:**  
Not necessary if room is well-ventilated.  
Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.
- **Body protection:** Protective work clothing

US

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 4)

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Fluid
· <b>Color:</b>	Red
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	Undetermined.

· **Flash point:** 120 °C (248 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** >270 °C (>518 °F) (DIN 51794)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

· <b>Lower:</b>	Not determined.
· <b>Upper:</b>	Not determined.

· **Vapor pressure:** Not determined.

· **Density at 20 °C (68 °F):** 0.881 g/cm<sup>3</sup> (7.352 lbs/gal) (ASTM D 4052)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	15.9 mm <sup>2</sup> /s @ 40 °C (60.6 mm <sup>2</sup> /s @ 104 °F)

· **Solvent separation test**

· **VOC content:** 0.04 %

· **Other information** No further relevant information available.

### 10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 5)

· **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:**

#### 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)

#### 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOEL	30-2,000 mg/kg/24h (rat)
	NOAEL	150 mg/kg/24h (mouse)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOEL	220 mg/m3 (rat)
	NOAEL	980 mg/m3 (rat)

#### 72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Oral	LD50	5,000 mg/kg (rat)
	LOAEL	125 mg/kg/24h (rat)
Dermal	LD50	2,000-5,000 mg/kg (rabbit)
	NOAEL	150 mg/kg/24h (mouse)
		30-2,000 mg/kg/24h (rat)
		1,000 mg/kg/24h (rabbit)
Inhalative	LOAEL	100 mg/kg/24h (mouse)
	LC50 / 4h	2.18-5.53 mg/l (rat)
	NOAEC	980 mg/m3 (rat)
	NOEC	220 mg/m3 (rat)

#### 64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, <0.03% aromatics

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
	NOAEL	25-125 mg/kg/24h (rat)

(Contd. on page 7)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 6)

Inhalative	LOAEL	1,000 mg/kg/24h (rabbit)
	LC50 / 4h	30 mg/kg/24h (rat)
	NOAEC	1.72-4.6 mg/l (rat)
	LOEL	880-1,710 mg/m <sup>3</sup> (rat)
		23-24 mg/m <sup>3</sup> (rat)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
140-88-5	ethyl acrylate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

**64742-53-6 Distillates (petroleum), hydrotreated light naphthenic**

LL50 10,000 mg/l/96h (aquatic invertebrates)  
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

**64742-53-6 Distillates (petroleum), hydrotreated light naphthenic**

LL50 10,000 mg/l/96h (aquatic invertebrates)  
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

LL50 10,000 mg/l/24h (aquatic invertebrates)

EL50 10,000 mg/l/48h (aquatic invertebrates)

**72623-87-1 Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based**

LL50 10,000 mg/l/96h (aquatic invertebrates)  
100 mg/l/96h (fish)

LL50 10,000 mg/l/72h (aquatic invertebrates)

LL50 10,000 mg/l/48h (aquatic invertebrates)

(Contd. on page 8)

US

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

**Trade name: FOX Suspension Fluid 4WT**

(Contd. of page 7)

LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)
<b>64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, &lt;0.03% aromatics</b>	
LL50	1.13-65 mg/l/96h (fish)
LL50	21-150 mg/l/72h (fish)
LL50	28-180 mg/l/48h (fish)
LL50	100-1,000 mg/l/24h (fish)
EL50	7.385-210 mg/l/48h (aquatic invertebrates)
EL50	180-1,000 mg/l/24h (aquatic invertebrates)
EL50	1.714-22 mg/l/72h (algae / cyanobacteria)

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**

· <b>Bioaccumulative potential</b>	
<b>64742-53-6 Distillates (petroleum), hydrotreated light naphthenic</b>	
Partition coefficient	2-6 [---] (log Kow) (Bioaccumulation)
<b>64742-53-6 Distillates (petroleum), hydrotreated light naphthenic</b>	
Partition coefficient	2-6 [---] (log Kow) (Bioaccumulation)
<b>64742-46-7 Hydrocarbons, C15-C20 n-alkanes, isoalkanes, cycloalkanes, &lt;0.03% aromatics</b>	
Biologische Abbaubarkeit	74 % (28d) (Biodegradability) (OECD 306)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Contact waste processors for recycling information.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, ADN, IMDG, IATA** Void

(Contd. on page 9)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 8)

- |  |                 |
|--|-----------------|
| · <b>UN proper shipping name</b>   | Void            |
| · <b>DOT, ADR/RID/ADN, ADN, IMDG, IATA</b>                                       | Void            |
| · <b>Transport hazard class(es)</b>  |                 |
| · <b>DOT, ADR/RID/ADN, ADN, IMDG, IATA</b>                                       | Void            |
| · <b>Class</b>   | Void            |
| · <b>Packing group</b>   |                 |
| · <b>DOT, ADR/RID/ADN, IMDG, IATA</b>  | Void            |
| · <b>Environmental hazards:</b>  |                 |
| · <b>Marine pollutant:</b>   | No              |
| · <b>Special precautions for user</b>  | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | Void            |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
100-41-4	ethylbenzene
140-88-5	ethyl acrylate

- **TSCA (Toxic Substances Control Act):**

97-88-1	n-butyl methacrylate	ACTIVE
142-16-5	Bis(2-ethylhexyl)maleat	ACTIVE
92257-31-3	2-Naphthalenol, 1-((4-(phenylazo)phenyl)azo)-, ar-heptylar, ar, Methyl derivative	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	ACTIVE
140-88-5	ethyl acrylate	ACTIVE

- **Hazardous Air Pollutants**

1330-20-7	xylene
100-41-4	ethylbenzene
140-88-5	ethyl acrylate

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
140-88-5	ethyl acrylate

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 03/30/2021

Reviewed on 03/30/2021

Trade name: **FOX Suspension Fluid 4WT**

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value)**

1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
140-88-5	ethyl acrylate	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

140-88-5 ethyl acrylate

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· **Department issuing SDS:** Abteilung Produktsicherheit

· **Contact:**

· **Date of preparation / last revision** 03/30/2021 / 1.2

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**